Kruge www.kruggusa.com

SVANGE 7236TLLR LED Medicine Cabinet - Specification Sheet

Features

- · Dimmable LED task lighting
- Integrated touch sensor control with memory
- Energy efficient LED lighting 5000K
- 11160 Lumens
- CRI 90+
- Integrated Defogger

Construction

- Quality polished edge mirror
- Single phase wire installation
- 5 MM Silver Backed Copper Free
- Installation Either Surface Mount
- (Side Mirror Trim Panels included) or Recessed
- Includes installation hardware

Codes/Standards Applicable


- Conforms to UL Std. 962
- Cert. to CSA Std. C22.2 No.250.0-08
- ETL Intertek 5004931

Electrical System

- 120Vac, 60Hz, 55W
- Electric Current: 0.45A
- Wattage: 55W

Model

- SVANGE 7236TLLR Swinging Door
- Included models in this configuration: Cabinet 1=2436L Cabinet 3=2436R Cabinet 2=2436L



Electrical System


- Perfomance Requirments: Contains the required
- Supervisory Circiut with the Auto-Monitoring Function as noted by UL 1310
- Input Voltage: Min 112Vac, Nom 125Vac, Max 137Vac
- Frequency:60Hz
- Front Receptacle Current: 102-132Vac Nominal 15A
- USB Output Current:5VDC Nominal 4A




CABINET CONFIGURATION

• Included models in this configuration: Cabinet 1 = 2436L Cabinet 2 = 2436L Cabinet 3 = 2436R


















SURFACE MOUNT







FRONT & BACKS

MODEL	А	В	С	D	E	F	G	Н	1
SVANGE 7236TLLR	36	72	24	24	24	34-1/2	67-1/2	11-1/4	1-1/8



RECESSED MOUNT






FRONT & BACKS

MODEL	А	В	С	D	E
SVANGE 7236TLLR	36	72	34-1/2	67-1/2	3-7/8






ELECTRICAL CORD LOCATIONS


MODEL	А	В	С	D
SVANGE 7236TLLR	1-1/2	1-1/8	1-3/8	11-1/4





DOOR & CABINET

MODEL	А	В	С	D	E	F	G
SVANGE 7236TLLR	7/8	3-7/8	4-3/4	18	3/8	5-1/4	11-1/4



INTERIOR CABINET

MODEL	А	В	С	D	Е	F	G	Н	I	J
SVANGE 7236TLLR	3-3/4	5-5/8	1-1/4	32-1/4	2-1/4	22-1/2	22-1/2	2-3/8	3/8	3-5/8